

CHRISTIE INSPIRE SERIES

PRELIMINARY

Boardrooms | Classrooms | Conference rooms

Performance-built, full-featured laser projectors

Our new Christie® Inspire Series is a family of feature-rich laser projectors designed for classrooms, boardrooms and other small or mid-sized environments. Combining built-in warping, blending, and camera-based alignment (Christie Twist™) and Christie Mystique™) with the reliability, performance, and operational life of 1DLP® and laser illumination, the Inspire Series offers amazing value without sacrificing advanced capabilities.

Unbeatable value

Featuring an advanced 1DLP laser illumination system, the Inspire Series provides up to 20,000 hours of reliable, virtually maintenance-free operation for a worry-free, low total cost of ownership.

Backed by a 3-year warranty and a price-point that won't break your budget, the Inspire Series is the easy choice for 6,000-8,000 ANSI lumen projectors.

Focused on features and quality

Proof that budget-friendly projectors don't need to sacrifice capabilities, the Inspire Series is a robust platform that stands up to the demands of professional applications. Featuring flexible input/output options, 2 on-board 10W speakers, built-in warping and blending, and a lightweight and dust-resistant design with whisper-quiet operation, the Inspire Series delivers amazing value.



CHRISTIE®

Technical specifications		DWU760-iS	DWU860-iS	DWU960-iS	DWU960ST-iS
Image	brightness	• 6000 ANSI lumens (typical) • 7,150 ISO lumens (typical)	• 7,200 ANSI lumens (typical) • 8,500 ISO lumens (typical)	• 8,100 ANSI lumens (typical) • 9,600 ISO lumens (typical)	• 8,100 ANSI lumens (typical) • 9,600 ISO lumens (typical)
	contrast ratio	• Full On/Off 1300:1 • RealBlack >1,300,000:1			
Display technology	type	• 1-chip 0.67" DMD S600HB			
	native resolution	• 1920 x 1200 WUXGA 16:10 aspect ratio			
Illumination	type	• High-efficiency blue laser phosphor			
	performance	• 20,000 hrs to 50% brightness			
Inputs	• HDMI (1.4a) • HDMI 2.0 • HDBaseT • 3D Sync In (BNC) • VGA • Audio In (3.5mm phone jack) • USB-A • IR Receiver				
Outputs	• 3D Sync In/Out (BNC) • HDMI • Audio Out (3.5mm phone jack)				
Warping and blending	standard	• Embedded Christie Twist™ warping and blending			
	optional	• Christie Mystique™ automated camera-based alignment (download Mystique Lite Edition at no additional cost)			
TAA compliant	• Yes		• No		
Speakers	• 2 x 10W				
Lens	type	• 1.25-2.0:1 (1.6x throw ratio) motorized lens - powered zoom, focus and offset			• 0.65-0.75:1 (1.1x zoom) motorized lens - powered zoom, focus and offset
	lens offset	• Vertical +/- 110% • Horizontal +/- 50%			• Vertical +/- 100% • Horizontal +/- 30%
	lens offset	• Vertical +/- 110% • Horizontal +/- 50%			
Displayable scanning frequency	scan rates	• TBD			
	max pixel clock rates	• 594 MHz (4096 x 2160); 162 MHz (1600 x 1200)			
Accessories	standard	• Power cable • Computer Cable • Lens cover and cap • IR remote controller (batteries not included)			
	optional	• Filter set • WiFi dongle • 3.5mm cable for wired remote functionality			
Power requirements	operating voltage	• 500W @ 110VAC input	• 660W @ 110VAC input		
	power consumption	• AC 100-240V, 50/60Hz			
	operating current	• 5A	• 6.5A		
	dissipation	• TBD			
Audible noise	• Typical 30 dBA • Eco mode 28 dBA		• Typical 34 dBA • Eco mode 32 dBA		• Typical 36 dBA • Eco mode 34 dBA
	size	• (LxWxH): 18.9 x 16 x 5.7" (480 x 406 x 157mm)			
Physical	shipping size	• 25.75 x 22.17 x 14.69" (654mm x 563mm x 373mm)			
	weight	• 29.8lbs (13.5kg)	• 30.2lbs (13.7kg)		
	shipping weight	• 36.8 lbs. (16.7kg)	• 37.9 lbs. (17.2kg)	• 37.4 lbs. (17 kg)	
	temperature	• 0-40°C			
Environment	humidity	• 10-85% RH			
	altitude	• 0-2,500ft @ 0°C-40°C • 2,500-5,000ft @ 0°C-35°C • 5,000-10,000ft @ 0°C-30°C			
	Regulatory	• Contact Christie for the timing of certifications: UL/CSA/IEC 60950-1, FCC Class A, CE, FDA, CCC, KC, PSE, CU, SABS, BIS, VCCI, RCM, Ukr, TER, SASO. • This product conforms to all relevant European directives, standards, safety, health and environmental concerns RoHS, REACH, WEEE			
Warranty	• 3 years parts and labor on the projector • 3 years or 20,000 hours parts and labor on the illumination system • Reference the Christie Standard Limited Warranty document for details • Or contact an authorized Christie representative for full details of our limited warranty				

The performance you need

- › **24/7 performance** – For continuous ‘all day, every day’ operation with industry-proven components that help ensure reliability
- › **IP5X dust-resistant** – Inspire’s airtight engine resists dust particles, ensures long-lasting reliability, and almost zero-maintenance performance
- › **Omnidirectional** – For image projection across a wide range of angles and directions, including the ceiling or floor
- › **Eco Mode** – Reduces brightness to 50%, significantly extends the lifetimes of your projector, and results in quieter operation (noise level)
- › **Built-in warping, blending, & alignment** – Christie Twist™ and Christie Mystique™ compatibility, for manual or automated camera-based warping, blending, and alignment
- › **AMX and Crestron connectivity** – For enhanced collaboration and easy integration into virtually any existing boardroom

For the most current specification information, please visit christiedigital.com

Copyright 2021 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. “Christie” is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD1996_Christie Inspire Series_DataSheet_Preliminary_May 21_EN

